

## About Us

Mint Energy develops energy generation and energy storage solutions to meet the ever-changing needs of modern-day consumers and businesses. Mint Energy strives to provide safe, environmentally-friendly, cost-effective, and reliable solutions.

---



## 12.6 kVAh Back-Up Power Supply

### Smart Battery Back-Up

The Back-Up Power Supply is an integrated battery back-up. The system collects and stores energy for access when and where it is needed most. Mint Energy's Graphene based solution reduces electricity costs while providing a safety net during blackouts for homes and businesses.

During power outages, the right energy storage solution allows businesses to avoid costly disruptions and continue business as normal. For homeowners, the Back-Up Power Supply can help prevent spoiled food and keep important appliances and medical devices running, even during extended outages. This helps consumers prevent temperature-related illness during rolling blackouts and outages caused by other factors.




### Why Graphene?

Unlike standard batteries which store energy chemically, The Mint Energy Graphene Supercapacitor stores energy electrostatically. The chemical reactions used to charge regular batteries work slowly and eventually cause the electrode materials to breakdown, our Supercapacitor is different. It can be recharged multiple times without wearing out.

- **Long lasting solution**
- **Quick charge/discharge**
- **Scalable solution**
- **Safer than lithium-ion**

---

## Contact us

-  +1 949 432-9091
-  [sales@mintenergy.com](mailto:sales@mintenergy.com)
-  895 Dove Street Suite 300  
Newport Beach, CA 92660 USA
-  [www.mintenergy.com](http://www.mintenergy.com)



BATTERY SPECIFICATION	UNIT	VALUE
Power Pack Banks	-	1
Module Series Capacitors	-	14
Module Parallel Capacitors	-	12
Module Total Capacitors	-	168
Total Power Pack Series Capacitors	-	14
Total Power Pack Parallel Capacitors	-	12
Total Power Pack Capacitors	-	168
Nominal Voltage	V	51.80
Rated Voltage	V	50.40
Max Surge Voltage	V	59.50
Max Continuous Voltage	V	58.80
Min Voltage	V	42.00
Nominal Current	A	120.00
Continuous Current	A	240.00
Peak Current (5 sec)	A	360.00
Maximum Continuous Discharging Current	A	136.27
Maximum Continuous Charging Current	A	60.00
Full to Empty Discharge Time at Maximum	Minutes	110.08
Empty to Full Charge Time at Maximum	Minutes	250.00
Maximum Inter-Cell Balance Discharge Current	mA	200.00
Overcharge Protection Cutoff Voltage Per Cell	V	4.25
Overcharge Protection Release Voltage Per Cell	V	4.18
Over-discharge Protection Cutoff Voltage Per Cell	V	3.80
Over-discharge Protection Release Voltage Per Cell	V	3.90
Low Temperature Cutoff Temperature	°F (°C)	5 (-15)
Low Temperature Release Temperature	°F (°C)	9 (-13)
High Temperature Cutoff Temperature	°F (°C)	131 (55)
High Temperature Release Temperature	°F (°C)	127 (53)
Total Cells Capacitance	f	7,870,128
Nominal Energy Rating	kVAh	12.60
Estimated Energy Storage (Watt Hours)	wh	12,600.00
Estimated Energy Storage (Amp Hours)	Ah	250.00
Self-Usage Power Consumption	VA	2.35
Internal Resistance	mΩ	1.75
Leakage Current	mA/h	46.667
Cycle Life	-	20,000



INVERTER SPECIFICATION	UNIT	VALUE
6 kVA Inverter/Charger	-	1
Instantaneous Power (100 ms)	VA	12,000
Surge Power (5 sec)	VA	9,000
Peak Power (30 min)	VA	6,600
Continuous Power Rating (@ 25°C)	VA	6,000
Nominal Power Rating	kVA	6
Nominal DC Input Voltage	VDC	48.0
DC Input Voltage Range	VDC	42 - 58.8
Waveform	-	Pure Sine Wave
AC Output Phase	-	Split/Single
AC Output Voltage (selectable)	VAC	120/240 (200-260)
AC Output Frequency (selectable)	Hz	60 (50)
Inverter Type	-	Low Frequency Transformer
Instantaneous AC Output Current (@ 25°C) (100ms)	AAC	50.0
Surge AC Output Current (@ 25°C) (5 sec)	AAC	37.5
Peak AC Output Current (@ 25°C) (30 min)	AAC	27.5
Continuous AC Output Current (@ 25°C)	AAC	25.0
Instantaneous DC Input Current (@ 25°C) (5 sec)	ADC	272.5
Surge DC Input Current (@ 25°C) (5 sec)	ADC	204.4
Peak DC Input Current (@ 25°C) (30 min)	ADC	149.9
Continuous DC Input Current (@ 25°C)	ADC	136.3
Self-Usage Power Consumption	VA	49.0
Typical Efficiency	-	85.0%
CEC Weighted Efficiency	-	84.0%
Total Harmonic Distortion	-	Typical: <2% Maximum: <5%
Output Voltage Regulation	-	±2%
AC Input Voltage Range	VAC	L1-L2: 184 to 272
AC Input Frequency Range	Hz	@ 60Hz: 54 to 66 @ 50Hz: 45 to 55
Grid-Interactive Voltage Range	-	L1-N or L2-N: 92 to 136VAC L1-L2: 184 to 272
Grid-Interactive Frequency Range	-	@ 60Hz: 59.7 to 60.3Hz
Maximum AC Input Current (@ 240VAC)	AAC	30.0
Maximum Utility Interactive Current	AAC	30.0
Continuous Battery Charge Output	ADC	60.0
Estimated Run Time 100% Load	Minutes	106.2
Estimated Run Time 50% Load	Minutes	212.4
Estimated Run Time 10% Load	Minutes	1,061.9

UNIT SPECIFICATIONS	UNIT	VALUE
Operating Temperature Range	°F (°C)	32 to 113 (-0 to 45)
Storage Temperature Range	°F (°C)	33 to 113 (-0 to 45)
Protection Class	-	Not Rated
Product Weight	Lbs. (kg)	437 (198.2)
Dimensions	in (mm)	50.79 (1290) x 38.98 (990) x 9.45 (240)